

BGH120

Industrial Range SINGLE RANGE TESTER

- ▶ Ranges from 1 to 120 bar
- ▶ Standard Accuracy to 0.015%
- ▶ Class 'A' Accuracy to 0.008%
- ▶ Supplied with integral pressure generation



The **BGH series base** can be used with any of the BGH series pistons to give ranges 1-120 bar with a BGH120, 2-300 bar with a BGH300, 1-700 bar with BGH700 and 1-1200 bar with BGH1200.

All units are top loading for ease of use and weight sets are fully interchangeable. This means that weight sets in alternative pressures are readily available and customers with more than one BGH series tester can interchange weight sets between testers of the same range.

The base features a dual area screwpress which allows low pressure priming and high pressure control. The BGH120 is a robust design, proven over many years usage. The unit has a 1/162 fully hardened stabilised tool steel piston.

This unit gives extremely good sensitivity for high accuracy calibration, yet is tough enough for regular use in a workshop environment.



Hydraulic Dead-Weight Testers.

Primary standards for Pressure Calibration

ACCURACY

All certificates issued for Budenberg Dead-weight Testers are fully traceable to national standards via equipment with UKAS calibration certificates. A standard accuracy of 0.015% is achieved from 10% of range using software supplied to compensate for the effects of gravity, temperature and the actual area of piston unit. Standard accuracy without any corrections for actual area is 0.02% from 12 to 120 bar, 0.03% from 1 to 12 bar. Higher accuracy Class A testers are available (supplied with UKAS Calibration certificates for area and mass) allowing an accuracy of 0.008% to be achieved.

| WEIGHTS SUPPLIED | | | | | |
|---|------|---------------------------|------|--|-----|
| bar or kg/cm ² Range 1-120 | | kPa Range 100-12000 | | lb/in ² Range 10-1600 | |
| Piston | 1 | Piston | 100 | Piston | 10 |
| 2 wts | 1 | 2 wts | 100 | 2 wts | 10 |
| 1 wt | 18 | 1 wt | 1800 | 1 wt | 180 |
| 4 wts | 20 | 4 wts | 2000 | 6 wts | 200 |
| 1 wt | 10 | 1 wt | 1000 | 1 wt | 100 |
| 2 wts | 4 | 2 wts | 400 | 2 wts | 40 |
| 1 wt | 2 | 1 wt | 200 | 1 wt | 20 |
| 1 wt | 0.5 | 1 wt | 50 | 1 wt | 5 |
| Optional fine increment weights | | | | | |
| 1 wt | 0.4 | 1 wt | 40 | 1 wt | 4 |
| 1 wt | 0.2 | 1wt | 20 | 1 wt | 2 |
| 1 wt | 0.1 | 1wt | 10 | 1 wt | 1 |
| 2 wts | 0.04 | 2 wts | 4 | 2 wts | 0.4 |
| 1 wt | 0.02 | 1wt | 2 | 1 wt | 0.2 |

SPARES, REPAIR AND RE-CERTIFICATION

Comprehensive service and calibration capability of both Budenberg and non Budenberg test equipment: Dead-weight Testers (working service or full overhaul). Portable calibrators (Budenberg & non- Budenberg).

Comparators.

All accuracy ranges can be supplied with UKAS Calibration Certificates.

Certification traceable to national standards. Rapid turn-around times and hire items available as a temporary replacement for strategically important plant.

ACCESSORIES

There are many accessories which can be supplied for use with the Dead-weight testers. These include liquid / liquid seals, two gauge stands and many others. Budenberg have extensive experience in the use of Dead-weight testers and can supply accessories for many applications. A separate data sheet of accessories is available.

PACKING DETAILS

1 carton containing base, tool roll and piston unit: 59 x 49 x 38cm. 0.110m³, Nett 20kg, Gross 22kg.
2 x cartons containing weights: 32 x 32 x 31cm. 0.04m³, Nett 25kg, Gross 30kg. ea



1/119 Delta Street Geebung QLD 4034
www.proconit.com.au
sales@proconit.com.au
07 3823 1922